


FORM PTO-1390 (REV 10-94)		U.S. Dept. of Commerce and Patent and Trademark Office	ATTORNEY'S DOCKET NUMBER: H01.2-9509
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371			U.S. APPLICATION NO. (if known): 09/673814
INTERNATIONAL APPLICATION NO.: PCT/EP99/02269	INTERNATIONAL FILING DATE (dd/mm/yy): 1 April 1999	PRIORITY DATE CLAIMED (dd/mm/yy): 22 April 1998	
TITLE OF INVENTION: COMPRESSED MEDIUM OPERATED NIPPERS			
APPLICANT(S) FOR DO/EO/US: Michael Kretzschmar			
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:			
1.	<input checked="" type="checkbox"/>	This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.	
2.	<input type="checkbox"/>	This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.	
3.	<input checked="" type="checkbox"/>	This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).	
4.	<input checked="" type="checkbox"/>	A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.	
5.	<input checked="" type="checkbox"/>	A copy of the International Application as filed (35 U.S.C. 371(c)(2))	
		a. <input type="checkbox"/> is transmitted herewith (required only if not transmitted by the International bureau).	
		b. <input checked="" type="checkbox"/> has been transmitted by the International Bureau.	
		c. <input type="checkbox"/> is not required, as the application was filed in the United States receiving Office (RO/US).	
6.	<input checked="" type="checkbox"/>	A translation of the International Application into English (35 U.S.C. 371 (c)(2)).	
7.	<input checked="" type="checkbox"/>	Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))	
		a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau).	
		b. <input type="checkbox"/> have been transmitted by the International Bureau.	
		c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired.	
		d. <input checked="" type="checkbox"/> have not been made and will not be made.	
8.	<input type="checkbox"/>	A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).	
9.	<input checked="" type="checkbox"/>	An oath or declaration of the inventor (35 U.S.C. 371(c)(4)).	
10.	<input type="checkbox"/>	A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).	
Items 11. to 16. below concern other document(s) or information included:			
11.	<input checked="" type="checkbox"/>	An Information Disclosure Statement under 37 CFR 1.97 and 1.98.	
12.	<input type="checkbox"/>	An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.29 and 3.31 is included.	
13.	<input checked="" type="checkbox"/>	A FIRST preliminary amendment. Please enter the amendment before fee calculation.	
	<input type="checkbox"/>	A SECOND or SUBSEQUENT preliminary amendment.	
14.	<input type="checkbox"/>	A substitute specification.	
15.	<input type="checkbox"/>	A change of power of attorney and/or address letter.	
16.	<input checked="" type="checkbox"/>	Other items or information: Translation of Amended Claims Under Article 34; Power of Attorney; Construction Petition; Correspondence Address document; Verified Statement Claiming Small Entity	

09/673814

422 Rec'd PCT/PTO 20 OCT 2000

17. <input checked="" type="checkbox"/> The following fees are submitted:				CALCULATIONS	PTO USE ONLY
BASIC NATIONAL FEE (37 CFR 1.492(A)(1)-(5)): <i>(select the appropriate one of the following fees)</i> Search Report has been prepared by the EPO or JPO \$ 930.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) \$ 490.00 No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)) \$ 750.00 Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$ 1,070.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Articles 33(2)-33(4) \$ 98.00 ENTER APPROPRIATE BASIC FEE AMOUNT =				\$930.00	
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				\$	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total Claims	30- 20 =	10	x \$ 22.00	\$220.00	
Independent Claims	1 - 3 =	0	x \$ 82.00	\$	
Multiple Dependent Claims (if applicable)			+ \$ 270.00	\$	
TOTAL OF ABOVE CALCULATIONS =				\$1150.00	
Reduction by 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must be filed also. (Note 37 CFR 1.9, 1.27, 1.28).				\$597.00	
SUBTOTAL =				\$575.00	
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$	
TOTAL NATIONAL FEE =				\$	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property				\$	
TOTAL FEES ENCLOSED =				\$575.00	
				Amount to be: Refunded	\$
				Charged	\$
<p style="text-align: center;">575.00</p> <p>a. <input checked="" type="checkbox"/> A check in the amount of \$ 637.00 to cover the above fees is enclosed.</p> <p>b. <input type="checkbox"/> Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees is enclosed. A duplicate copy of this sheet is enclosed.</p> <p>c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 22-0350.</p>					
Send All Correspondence To: Vidas, Arrett & Steinkraus, P.A. Suite 2000 6109 Blue Circle Drive Minnetonka, MN 55343-9131 Telephone: (952) 563-3000 Facsimile: (952) 563-3001				By:  RICHARD A. ARRETT, ESQ. Registration No. 33,153	

PATENT/DESIGN PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventor: **Dr.** KRETZSCHMAR, Michael)
 Title: **COMPRESSED-MEDIUM OPERATED NIPPERS**)
 Filed: ☒ Concurrently herewith)
 ☐ on _____)
 Ser. No. _____)

VERIFIED STATEMENT
 CLAIMING
 SMALL ENTITY STATUS

(INVENTOR FORM)

Docket No: **H01-0-9509**

1. As a below-named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR §1.9(c) for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention identified above, the docket no., filing date and application number of which application may be inserted above by any attorney of Vidas, Arrett & Steinkraus, P.A., when known.

2. I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR §1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR § 1.9(d) or a nonprofit organization under 37 CFR §1.9(e)

3. I acknowledge the duty to file, in this application for patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate.

4. I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Dated: **6.** October, 2000

Signature 
 Inventor Name: **Dr. Kretzschmar, Michael**

Dated: _____

Signature _____
 Inventor Name: _____

Dated: _____

Signature _____
 Inventor Name: _____

(Attach further sheets for additional inventor)
 (Filing date, serial number and docket number may be left blank at time of signing)

VIDAS, ARRETT & STEINKRAUS
 Suite 2000 6109 Blue Circle Drive, Minnetonka, Minnesota 55343-9131, USA
 Phone (612) 563-3000 Facsimile (612) 563 3001

000207-118E2960

Variable	Mean	SD	Min	Max
Age	34.5	10.2	21	55
Gender	0.5	0.5	0	1
Marital status	0.6	0.5	0	1
Education	12.5	1.5	9	16
Income	1500	500	500	3000
Health status	0.8	0.2	0	1
Smoking status	0.3	0.5	0	1
Alcohol consumption	0.2	0.4	0	1
Exercise frequency	0.5	0.5	0	1
Stress level	0.7	0.3	0	1
Sleep quality	0.6	0.4	0	1
Work satisfaction	0.5	0.5	0	1
Life satisfaction	0.6	0.4	0	1
Depression score	0.3	0.5	0	1
Anxiety score	0.2	0.4	0	1
Quality of life	0.7	0.3	0	1
Healthcare utilization	0.4	0.5	0	1
Health insurance status	0.9	0.1	0	1
Chronic disease status	0.1	0.3	0	1
Family size	2.5	1.0	1	5
Home ownership	0.7	0.4	0	1
Commute time	30	15	10	60
Neighborhood safety	0.8	0.2	0	1
Access to healthcare	0.9	0.1	0	1
Healthcare costs	1000	300	500	2000
Healthcare quality	0.8	0.2	0	1
Healthcare access	0.9	0.1	0	1
Healthcare satisfaction	0.7	0.3	0	1
Healthcare utilization frequency	0.5	0.5	0	1
Healthcare utilization cost	500	200	200	1000
Healthcare utilization quality	0.8	0.2	0	1
Healthcare utilization access	0.9	0.1	0	1
Healthcare utilization satisfaction	0.7	0.3	0	1
Healthcare utilization frequency	0.5	0.5	0	1
Healthcare utilization cost	500	200	200	1000
Healthcare utilization quality	0.8	0.2	0	1
Healthcare utilization access	0.9	0.1	0	1
Healthcare utilization satisfaction	0.7	0.3	0	1

Compressed-medium operated nippers

The invention relates to compressed-medium operated nippers for locking rings, clips, studs, cable lugs, and the like according to the preamble of claim 1. Generally, the compressed-medium operated nippers are suited for any objects that are squeezed in place.

Compressed-medium operated nippers specifically serve for permanently deforming locking rings so that they clip one part to another, e.g. a hose to a socket. For example, they are used in automobile manufacture. From DE 195 19 543 C2, compressed-medium operated nippers of the aforementioned type are known which have a compressed-medium connection point and a compressed-medium valve connected thereto, several driving pistons separated from each other which are controlled by the compressed-medium valve, a feed member adapted to be driven by the driving piston, and pivotally supported nipper insert halves the inner lever ends of which are engaged by the feed member to swivel them. These compressed-medium operated nippers are intended to ensure that the closing gap required for the nipper insert halves be reached while under a full build-up of forces and that a influence not dependent on the working pressure be favourably exerted on the closing forces. To this effect, the compressed-medium valve has a valve stem slidably guided in a direction transverse to the piston motion and which is adapted to be actuated by a release mechanism which, when in a rest position, blocks the connection of the driving pistons to the compressed-medium connection point and joins these to a lower pressure level and which, when in a working position achievable by an actuation of the release mechanism, blocks the connection of the driving pistons to the lower pressure level and joins these to the compressed-medium connection point. What adds to this is that a connecting rod is kept movable in a guide extending in the direction of motion of the driving pistons and is biased by a spring towards the valve stem wherein the connecting rod has an outer offset as a driver and the driving piston has a transpierced shank receiving the connecting rod with an inner offset associated with the outer offset as a stop for carrying along the

connecting rod in the last section in its motion to close the nipper insert halves. For this purpose, the valve stem has a blocking seat in which the connecting rod is caught under the action of the spring while the valve stem is moving from the rest position to the work position and from which the connecting rod is released while being carried along by the driving piston. Consequently, the piston is always displaced by force from its initial position to a final position in which the nippers reach the required closing gap for an adequate duration of closure.

A particular ease in mounting and a modular adaptability of these compressed-medium operated nippers to varying force requirements are reached by the fact that the housing between the compressed-medium valve and the adjoining positioned driving piston has fixed in it a partition wall on which the spring which biases the valve stem is supported. It is reached by the further fact that the driving piston which is disposed next to the partition wall and is adjacent to the compressed-medium valve is T-shaped and supports the shank which is directed to the feed member and has the inner offset, on the succeeding driving piston. Hence, the devices for engaging and carrying along the connecting rod are limited to the partition wall and the adjoining driving piston. The other driving pistons may be manufactured, mounted, and serially staggered regardless of this, in the number necessary for the closing force required.

However, faulty mountings may occur also for these nippers, for example, if the fitter wrongly places the nippers on the locking ring or pressure variations are encountered in the compressed-medium network, which mostly is a compressed-air network.

A press-in effect monitoring system is known from the leaflet "Preßkraft-Meß- und Regeleinrichtung Typ SEP" of the Tox-Preßtechnik Company, Weingarten, received on July 21st, 1993, which system is employed on a press and can be delivered only along with a complete press. This state of the art discloses how to regulate and measure pressing forces in press-in and deforming operations,

for which purpose the real value is determined via an oil pressure sensor or force sensor and is fed, as a set value, to the proportional valve. What is depicted in details is how to use an oil pressure sensor. Details of how to use a force sensor cannot be deduced from this publication.

A multi-finger gripper which detects the gripping force and spatial reaction forces and moments is known from AT 395 124 B. It comprises a gripper housing, a trapezoidal spindle, and a restricted-guidance sliding block including a guide groove in which the toggle levers of parallelogram linkages to which grip fingers are fastened are guided. The pivots of the toggle levers of parallelogram linkages are axisymmetrically and uniformly spaced circumferentially on the inner ring of a deforming body of a force and torque feeler which is known per sé. This one comprises an inner ring, an outer ring fixed to the gripper housing, elastic elements interconnecting the two rings, and measured-data transmitters registering the deformation of the elastic elements. This registration of measured data which is based on the registration of reaction forces and moments on gear bearings of grip fingers is expensive, requires a lot of space, and is relatively inaccurate.

DE 21 18 782 C2 relates to a compressed-medium operated clipping tool to obtain pressure-sealed pipe connections, which is operated by a hand-actuated hydraulic pump. A pressure gauge responds to the pressure produced by the pump, is supervised by the operator, and signals the termination of the deforming process. This measuring device displays the force applied by clamping jaws to the pipes being locked with each other only in a relatively inaccurate manner.

Accordingly, it is the object of the invention to provide compressed-medium operated nippers which enable the mounting of locking rings and the like in a further improved quality with a view to reducing the expenditure in verifying the mounting of locking rings.

The object is attained by compressed-medium operated nippers having the features of claim 1. Advantageous aspects of the compressed-medium operated

nippers, which preferably are designed as a hand-held device, are indicated in the sub-claims.

The solution is characterized in that a force sensor is disposed in the flux of forces between the driving piston and the nipper insert halves for measuring a force dependent on the closing force of the nipper insert halves. Preferably, the force sensor on the feed member measures a force dependent on the closing force of the nipper insert halves. For this purpose, it may be mounted on the feed member or may be integrated therein. In addition, the compressed-medium operated nippers may be connected to an evaluation device which may be integrated in the compressed-medium operated nippers or may also be disposed outside the compressed-medium operated nippers. In particular, the evaluation device may serve for controlling a display and/or turning off the pair of nippers upon non-observance of a value preset for the closing force and/or for controlling the pressure of the compressed medium up to a value ensuring the attainment of a value preset for the closing force and/or for feeding the values measured to a documentation device for documenting the closing force. To this effect, the evaluation device may have appropriate devices or, in turn, may be connected to these.

The invention relies on the finding that the closing force of the nipper insert halves, i.e. the force applied by the nipper insert halves to a locking ring or the like, is dependent on the force encountered between the driving piston and the nipper insert halves. In particular, it was found that the force in the feed member, which preferably abuts, at a tapering front end which may be wedge-shaped or parabola-shaped, against the inner lever ends of the nipper insert halves and may be bolted to a piston at the other end, exhibits an almost ideal, linear dependence on the closing force. Hence, the closing force may be determined very precisely via the force sensor. What adds to this is that its arrangement in the flux of forces between the driving piston and the nipper insert halves does not interfere with mounting because it does not engage into the working range of the nipper insert halves. On the other

hand, it does not interfere either with the pressure buildup in the area of the driving pistons. In addition, it permits a unit-assembly system using compressed-medium operated nippers in which the measurement of forces may be carried out in an identical manner and which differ merely by their number of serially staggered pistons that is chosen depending on the closing force desired.

The force measured by the force sensor is utilizable in different ways within the scope of the invention. Thus, it may be utilized by an evaluation device for controlling a display such as an optical and/or acoustical display, and/or for turning off the compressed-medium operated nippers every time upon non-observance of the value preset for the closing force. The value preset for the closing force may be a minimum force which requires to be reached by all means. However, it also may be a maximum force or a minimum force and a maximum force which require to be observed at the same time. For example, if the nipper insert halves only act upon a marginal area of a locking zone of the locking ring the closing force reached will be only a fraction of the closing force that would be built up if the complete locking zone was acted on. However, in the event that the nipper insert halves are applied to a wrong zone of the locking ring, which is more difficult to deform than the nippers, an excessive closing force will result. The evaluation device is capable of detecting and signaling this and/or may turn off the compressed-medium operated nippers before time so that the operator may instantly recognize and correct the error.

In addition or instead, the evaluation device may control the pressure of the compressed medium causing the driving pistons to be driven so as to observe a value preset for the closing force. For this purpose, the evaluation device may resort to a pressure control valve which can be associated with the compressed-medium connection point and, at the same time, may be the compressed-medium valve which controls the motion of the driving pistons.

In addition or instead, the force measured may be documented by a documentation device such as a plotter and/or a PC having an electronic memory.

which, for example, may lead to a destruction of the components requiring to be interconnected. Also, the preset value may comprise a minimum pressure and a maximum pressure. The evaluation device, by emitting an optical or acoustic display or turning off the compressed-medium nippers, informs the operator that the pressure required for mounting does not exist, which avoids faulty mountings. The latter, however, may also be avoided by the fact that the pressure sensor controls the pressure of the compressed medium via a regulation device. Thus, the pressure sensor may cause a pressure regulation unit to increase or decrease the feed pressure for the compressed-medium operated nippers. Finally, it is also possible to document the pressure by means of a documentation device in order to obtain a quality proof for the mounting of the locking ring in addition to error analysis and error avoidance.

It is preferred that the two solution variants are jointly realized in compressed-medium operated nippers. Further, compressed-medium operated nippers according to one of the solution variants or the combination thereof may be provided with the features of the compressed-medium operated nippers according to DE 195 19 543 C2 which ensures that the appropriate closing gap is achieved. This makes possible compressed-medium operated nippers which ensure that whenever a locking ring is mounted

- the compressed-medium pressure required is available
- the closing gap required is achieved, and
- the closing force assumes the correct values.

The invention will now be explained in greater detail with reference to the accompanying drawing of an embodiment of the compressed-medium operated nippers for the manual mode of operation. In the drawing,

Fig. 1 shows the compressed-medium operated nippers, partially in a longitudinal section, with details of the control portion omitted;

[illegible][illegible][illegible][illegible]

place below it a hose 28 which is led away rearwards and in which the connecting cable 21 is led to an evaluation device and/or a documentation device. Instead, it will also be possible to accommodate an evaluation device and/or documentation device directly in or on the compressed-medium operated nippers.

The driving range 2 further comprises an array of serially staggered pistons. These include a disk-shaped driving piston 29 which is fixed by means of a bolt 30 to the rear front-end face of the portion 17" of the feed member 17. The driving piston 29 is circumferentially sealed towards the housing 8 and is guided therein in an axial movable relationship.

Seated at the outside of the portion 17", next to the piston 29, is a sleeve 31 which, acting as a stop, limits the motion of the driving piston 29 to the nipper head 15. Thus, the sleeve 15 protects a helical return spring 32 which is supported on the driving piston 29, at one end, and on the nipper head 5, at the other end and tries to force the driving piston 29 away from the nipper head 5. The return spring 32 urges the driving piston 29, when relieved from pressure, up to a ring washer shaped partition wall 32 which is fixed in the housing 8. Also fixed in the housing 8 are another partition wall 33 at a distance from the partition wall 32 and yet another partition wall 34 at an adequate distance from the partition wall 33.

The central apertures of the ring washer shaped partition walls 32, 33, 34 have sealingly guided therein shanks 35, 36, 37 each of T-shaped driving pistons 38, 39, 40. These have piston disks 41, 42, 43 which are circumferentially guided in the housing 8 in a sealing relationship and are axially movable therein. Because the driving pistons 38, 39, 40 are supported on the driving piston 29 and also support each other they will be shifted back, when relieved from pressure, by the return spring 32 until they bear against the partition walls 33, 34 and a shoulder 44 of the control range 4.

The driving pistons 38, 39, 40 are provided with central, axially directed through bores 45, 46, 47 which communicate with recesses 48, 49, 50 at the ends of

When the nipper insert tips 14 of the nipper insert halves 13 are swiveled together a force is transmitted, via the feed member 17, which is also transmitted via the force sensor 19 in a shunt. This force is linearly dependent upon the closing force effective between the nipper insert tips 14. It is subjected to evaluation and documentation via the connecting cable 21, which provides for a check of the quality in clip mounting.

Additionally, the compressed air fed to the compressed-medium connection point 56 is monitored via a pressure sensor 57 disposed in the control range 4 or disposed externally in order that if the pressure falls below the preset minimum or exceeds a preset maximum the mounting of a locking ring is prevented or corrected, in which case the air pressure is automatically re-adjusted, if necessary. The pressure sensor 57 is connected, via a further connecting cable 58, with an evaluation device and/or change-over device and/or regulating device and/or documentation device which is external here.

The embodiment makes it evident that if a desired closing force is to be achieved it is merely the number of serially staggered pistons 29, 38, 39, 40 and, accordingly, the length of the housing 8 which needs to be changed. It is always the same feed member 17 with its integrated force sensor 19 which can be employed here, and the working range 1 and the control range 4 need not be changed.

Amended Claims 1 to 30Claims

1. Compressed-medium operated nippers for locking rings and the like, comprising a control range (4) with a compressed-medium connection point (56) and a compressed-medium valve connected thereto, at least one driving piston (29) controlled by the compressed-medium valve, and a working range (1) with a feed member (17) adapted to be driven by the driving piston (29) and pivotally supported nipper insert halves (13) the inner lever ends of which are engaged by the feed member (17) to swivel them, characterized in that a force sensor (19) is disposed in the flux of forces between the driving piston (29) and the nipper insert halves (13) for measuring a force dependent on the closing force of the nipper insert halves (13) and that the force sensor (19) is integrated in the feed member (17).
2. The compressed-medium operated nippers according to claim 1, characterized in that the force sensor (19) is of a plate shape and is disposed transversely to the flux of forces on the feed member (17).
3. The compressed-medium operated nippers according to claim 2, characterized in that the cross-section of the force sensor (19) is approximately congruent with the maximum cross-section of the feed member (17).
4. The compressed-medium operated nippers according to claims 1 to 3, characterized in that the force sensor (19) is held at a central hole of a stud (18) extending in the direction of the flux of forces and which is anchored in the feed member.

.../2

5. The compressed-medium operated nippers according to any one of claims 1 to 4, characterized in that the force sensor (19) is disposed between a portion (17'') interacting with the driving piston (29) and a portion (17') of the feed member (17) interacting with the lever ends of the nipper insert halves (13).
6. The compressed-medium operated nippers according to claims 4 and 5, characterized in that the stud (18) is anchored, at its two ends, in the two portions (17', 17'') of the feed member (17) and holds the force sensor (19) between the two portions (17', 17'') of the feed member (17).
7. The compressed-medium operated nippers according to any one of claims 4 to 6, characterized in that the force sensor (19) is of a ring washer shape.
8. The compressed-medium operated nippers according to any one of claims 4 to 7, characterized in that perforated disks (20) are seated on the stud (18) at either side of the force sensor (19) and that the flux of forces through the force sensor (19) is effected via the perforated disks (20).
9. The compressed-medium operated nippers according to claim 8, characterized in that the perforated disks are ring washers (20).
10. The compressed-medium operated nippers according to any one of claims 1 to 9, characterized in that the force sensor (19) is mounted on the feed member (17) under a bias.

11. The compressed-medium operated nippers according to claim 10, characterized in that the force sensor (19) is biased in the feed member (17) by bolting the stud (18).
12. The compressed-medium operated nippers according to any one of claims 4 to 11, characterized in that a bolting of the stud (18) in the feed member (17) has an anti-rotation lock.
13. The compressed-medium operated nippers according to any one of claims 1 to 12, characterized in that a flexible connecting cable (21) of the force sensor (19) is led out through a slot (22) extending in the direction of motion of the feed member (17) in a housing portion (5) accommodating it.
14. The compressed-medium operated nippers according to claim 13, characterized in that the slot (22) extends across the whole zone of motion of the force sensor (19) with the feed member (17).
15. The compressed-medium operated nippers according to claim 13 or 14, characterized in that the portion of the connecting cable (21) that is led out is fixed to the housing (8).
16. The compressed-medium operated nippers according to any one of claims 13 to 15, characterized in that the slot (22) is firmly covered externally on the housing by a hood (23) which has a cavity (25) in which the connecting cable (21) is designed to undergo deformation while the feed member (17) is being displaced.

17. The compressed-medium operated nippers according to any one of claims 1 to 16, characterized in that a connecting cable (21) of the force sensor (19), while connected to a compressed-medium hose, is led way from the compressed-medium operated nippers.
18. The compressed-medium operated nippers according to any one of claims 1 to 17, characterized in that the force sensor (19) is a foil strain gauge (FSG) sensor and/or a piezosensor.
19. The compressed-medium operated nippers according to any one of claims 1 to 18, characterized in that they have a pressure sensor (57) to monitor the pressure of the compressed medium and that the pressure sensor (57) is connected to an evaluation device.
20. The compressed-medium operated nippers according to claim 19, characterized in that the pressure sensor (57) is integrated in the compressed-medium valve.
21. The compressed-medium operated nippers according to claim 19, characterized in that the pressure sensor (57) is integrated in the compressed-medium connection point (56).
22. The compressed-medium operated nippers according to claim 19, characterized in that the pressure sensor (57) is integrated in a compressed-medium line joined to the compressed-medium connection point (56).

23. The compressed-medium operated nippers according to any one of claims 1 to 20, characterized in that the force sensor (19) and/or the pressure sensor (57) are/is connected to an evaluation device.
24. The compressed-medium operated nippers according to claim 23, characterized in that the evaluation device controls a display for the closing force and/or the pressure of the compressed medium and/or controls means to turn off the compressed-medium operated nippers upon non-observance of a value preset for the closing force and/or a value preset for the pressure and/or controls means to adjust the pressure until a preset rate is reached for the closing force and/or for the pressure and/or feeds the values measured for the closing force and/or the pressure to the documentation device.
25. The compressed-medium operated nippers according to claim 23 or 24, characterized in that the display is an optical and/or acoustic display.
26. The compressed-medium operated nippers according to any one of claims 23 to 25, characterized in that the evaluation device and/or the devices fed thereby are electric devices.
27. The compressed-medium operated nippers according to any one of claims 1 to 26, characterized in that they are designed as a hand-held apparatus.
28. The compressed-medium operated nippers according to any one of claims 1 to 27, characterized in that if the working range (1), the control range (4), and the feed member (17) with the force sensor (19) integrated are identical a series of driving ranges including different numbers of serially staggered

.../6

driving pistons (29, 38, 39, 40) are provided to achieve different closing forces.

29. A unit-assembly system including compressed-medium operated nippers according to any one of claims 1 to 28, characterized in that it comprises compressed-medium operated nippers which have different numbers of serially staggered driving pistons (29, 38, 39, 40) wherein, however, the feed member (17) with the force sensor (19), a working range (1) including the nipper insert halves (13) and a control range (4) including a release lever (55) and a compressed-medium valve coincide with each other.
30. The unit-assembly system including compressed-medium operated nippers according to any one of claims 1 to 29, characterized in that they comprise compressed-medium operated nippers with a force sensor and/or a pressure sensor and/or an evaluation device and/or a display and/or turn-off means and/or pressure control means and/or a documentation device.

Abstract

Compressed-medium operated nippers

Compressed-medium operated nippers for locking rings and the like, comprising a control range with a compressed-medium connection point and a compressed-medium valve connected thereto, at least one driving piston controlled by the compressed-medium valve, and a working range with a feed member adapted to be driven by the driving piston and pivotally supported nipper insert halves the inner lever ends of which are engaged by the feed member to swivel them wherein a force sensor is disposed in the flux of forces between the driving piston and the nipper insert halves for measuring a force dependent on the closing force of the nipper insert halves.

DECLARATION

PATENT/DESIGN PATENT

As a below-named inventor, I(we) hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name;

I verily believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

COMPRESSED-MEDIUM OPERATED NIPPERS

(Insert invention title)

the specification of which is attached hereto.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to in the declaration.

I acknowledge the duty to disclose all information which is known to be material to patentability of this application in accordance with Title 37, Code of Federal Regulations § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119, of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

(List prior foreign applications)

COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 37 USC 119
Germany	198 18 029.2	22 / 04 / 1998	[X] YES NO []
			[] YES NO []
			[] YES NO []

I hereby declare that all statements made herein of my knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Telephone calls and correspondence should be directed to:

VIDAS, ARRETT & STEINKRAUS
Suite 2000, 6109 Blue Circle Drive, Minnetonka, Minnesota 55343-9131, USA
Phone (612) 563 3000 Facsimile (612) 563 3001

Sole or First Inventor

Second Inventor

Full name: Dr. KRETZSCHMAR, Michael
Inventor's
signature: [Signature]
Date: 27 October, 2000
Citizenship: German
Post office
address: Heseltücken 18
D-22453 Hamburg
Germany
Residence:
(if different from
post office address)

Full name: _____
Inventor's
signature: _____
Date: _____
Citizenship: _____
Post office
address: _____
Residence
(if different from
post office address)

(Attach additional sheets for third and subsequent inventors)

09673814.100000

PATENT/DESIGN PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventor: *Dr.* KRETZSCHMAR, Michael

**POWER OF ATTORNEY
FROM INVENTOR(S)**

Title: COMPRESSED-MEDIUM OPERATED NIPPERS

Filed: [X] Concurrently Herewith
[] on _____
Ser. No. _____

Box: PATENT APPLICATION
Assistant Commissioner for Patents
Washington, DC 20231

Docket No: H01.2.9509

As a below named inventor of the subject matter of the above identified patent application, I hereby appoint the following attorneys to insert the docket no., filing date and application number of said application above when known; to prosecute this application and any application claiming priority therefrom; to execute any terminal disclaimers on behalf of assignee; and to transact all business in the Patent and Trademark Office connected therewith:

Oliver F. Arrett	Reg. No. 22,117
Scott Q. Vidas	Reg. No. 30,812
Walter J. Steinkraus	Reg. No. 29,592
Richard A. Arrett	Reg. No. 33,153
Leoniede M. Brennan	Reg. No. 35,832
Jane H. Arrett	Reg. No. 33,355
William E. Anderson II	Reg. No. 37,766
Jonathan Grad	Reg. No. 41,795
Robert O. Vidas	Reg. No. 20,164

all of VIDAS, ARRETT & STEINKRAUS, Professional Association, Suite 2000, 6109 Blue Circle Drive, Minnetonka, Minnesota, USA, Telephone (612) 563 3000, and I hereby authorize them to act and rely on instructions from, and to communicate directly with, the firm or person which sent this case to VIDAS, ARRETT & STEINKRAUS unless or until I instruct VIDAS, ARRETT & STEINKRAUS in writing to the contrary.

Dated this 6 day of October 2000

(First inventor's signature)

(First inventor's name) **Dr. Kretzschmar, Michael**

(Second inventor's signature)

(Second inventor's name)

(Third inventor's signature)

(Third inventor's name)

Attach additional sheet with name(s) and signature(s) of fourth and subsequent inventors
(Filing date, serial number and docket number may be left blank at time of signing)

VIDAS, ARRETT & STEINKRAUS
Suite 2000 6109 Blue Circle Drive, Minnetonka, Minnesota 55343-9131, USA
Phone (612) 563-3000 Facsimile (612) 563 3001

09/673814

422 Rec'd PCT/PTO 20 OCT 2000

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
UNITED STATES RECEIVING OFFICE (RO/US)

In re Application of:	Michael Kretzschmar
U.S. Nat'l Stage of	PCT/EP99/02269
Int'l App. No.:	
Int'l Filing Date:	1 April 1999
For:	COMPRESSED MEDIUM OPERATED NIPPERS

Box PCT
ATTN: EO/US
Assistant Commissioner for Patents
Washington, D.C. 20231

Docket No.: H01.2-9509

CORRESPONDENCE ADDRESS OF LAW FIRM

Vidas, Arrett & Steinkraus P.A. would like to make the following correspondence address of record. Please send all correspondence for this application to the address as follows:


CUSTOMER NUMBER 490

whose present address is
Vidas, Arrett & Steinkraus P.A.
Suite 2000
6109 Blue Circle Drive
Minnetonka, MN 55343-9131

Respectfully submitted,

VIDAS, ARRETT & STEINKRAUS

By:



RICHARD A. ARRETT, ESQ.
Registration No. 33,153

Suite 2000
6109 Blue Circle Drive
Minnetonka, MN 55343-9185
Phone: (952) 563-3000
Facsimile: (952) 563-3001

000207 "476E2960